

## FOUNDATION

# RESISTO

### The FOUNDATION/ICF WATERPROOFING MEMBRANE

is a 40-mil-thick self-adhesive membrane composed of elastomeric bitumen and a trilaminate woven polyethylene.

The bottom, self-adhesive surface is covered with an easy-to-remove silicone-coated release sheet.

FOUNDATION / ICF WATERPROOFING MEMBRANE has been specially developed for ICF foundation waterproofing.



# FOUNDATION/ICF

## WATERPROOFING MEMBRANE

SELF-ADHESIVE ELASTOMERIC



# RESISTO

- Specially designed peel and stick formulation
- No primer required\*
- Superior adherence
- Consistent thickness
- UV resistant (90 days exposure)
- High puncture resistance
- Effective and hard-wearing
- Clean and easy installation
- Requires no special tools

*Solvent-base primers may damage polystyrene and therefore must not be used.*

*\* A water-based primer is optional only on ICF foundations.*

# FOUNDATION

## RESISTO FOUNDATION/ICF WATERPROOFING MEMBRANE

UPC Code : WINTER : 6 23680 10133 3  
SUMMER : 6 23680 10134 0

Product code	Dimensions	Thickness mil / mm	Approximate surface covered					
			per roll		per box		per pallet	
			ft <sup>2</sup>	m <sup>2</sup>	ft <sup>2</sup>	m <sup>2</sup>	ft <sup>2</sup>	m <sup>2</sup>
10133 <b>WINTER</b>	36" x 75' 91 cm x 22,9 m	40 / 1.0	225	20.8	225	20.8	5,625	520
10134 <b>SUMMER</b>	36" x 75' 91 cm x 22,9 m	40 / 1.0	225	20.8	225	20.8	5,625	520

Units per box : 1

Boxes per pallet : 25

Weight (±) per pallet : 1,066 lbs / 483.5 Kg

### RECOMMENDED USES

- ICF foundations (expanded or extruded polystyrene)
- Concrete foundations (primer required)

### INSTALLATION TEMPERATURE

- WINTER grade : 14 °F to 160 °F (-10 °C to 70 °C)
- SUMMER grade : 50 °F to 185 °F (10 °C to 85 °C)

### REQUIRED PRODUCT



# FOUNDATION/ICF

## WATERPROOFING MEMBRANE

SELF-ADHESIVE ELASTOMERIC



RESISTO



PRINTED IN CANADA • AR046-032008

**RESISTO**  
WATERPROOFING SOLUTIONS

CUSTOMER SERVICE  
**1 877 478.8408**  
[www.resisto.ca](http://www.resisto.ca)